EXPLORER 727

COBHAM

Comms-on-the-move Inmarsat BGAN terminal

February 2016 Product Sheet

The most important thing we build is trust



EXPLORER 727

Comms-on-the-move BGAN terminal

Comprehensive communcation hub for vehicles

EXPLORER 727 is a high-speed, vehicular broadband system. It consists of three fully integrated units – a transceiver, an IP handset and a roof mountable antenna.

Live media broadcast, defense or humanitarian operations requires communication equipment that you can always rely on. With EXPLORER 727 you get the most comprehensive and best in class Mobile Communication Hub.



Specifications

Transceiver H / W / D:

42.5 / 231 / 273 mm 1 67 / 9 72 / 10 63 inches

Antenna H / W: 152 / Ø477 mm

6.3 / Ø18.76 inches

Weight

Antenna: Transceiver:

6 kg / 13.2 lbs 2.5 kg / 5.5 lbs

Global Services

Voice. 4 khns AMRF+2

3.1 kHz audio, 64 kbps Premium voice

Standard IP: Up to 492 kbps

Streaming IP: 32, 64, 128, 256 kbps

BGAN X-Stream: Min. 384 kbps on-the-pause

ISDN UDI 64 kbps / RDI 56 kbps

SMS: 160 characters

Guaranteed service: Works above 5° elevation

1525.0 - 1559.0 MHz (Rx) Inmarsat frequencies:

1626.5 - 1660.5 MHz (Tx)

Recommended antenna cable

20 dB@1.62 GHz & Cable loss max / min:

 1Ω DC loop resistance

3 dB @ 36 MHz / 4 dB @ 54 MHz

The antenna automatically tracks satellite positions enabling high-speed connectivity while on-the-move. Up to 492 kbps data & simultaneous phone

Mobile Communication

Place the antenna on the roof of your vehicle to turn it into a complete mobile communication hub. Provides access to the

High-speed broadband on-the-Move

even at speeds in excess of 200 km/h.

internet and phone networks instantly.

User Interface: Power On/Off button. DC power input connector with Remote

> on/off and locking mechanism. Status LEDs for Power, Tran-

> sceiver, Antenna, and Messages. Thrane & Thrane web interface. Factory default reset

Languages: UK, FR, DE, ES, RU and CN

Approvals: CE, GMPCS, FCC

> Inmarsat Land Class 10 Type Approval (Vehicular)

IEEE 802.3 (1998 edition)

2 x Analogue RJ-11 phone/fax interfaces

4 x LAN interfaces

RJ-45 Connector type:

Power over Ethernet (PoE) 10/100 Mbps 100m / 328ft (Cat5 LITP)

Max. cable length: Standard: ISO/IEC 8877:1992 and

1 x ISDN interface

Connector type:

I/O connector: 5 pin general purpose I/O

Antenna Connector: Transceiver, TNC-Socket, Female

Antenna, TNC-Socket, Female

BGAN SIM-Card slot

Environmental conditions

Temperature

-25 to +55°C / -13 to 131°F Operational: Survival: -40 to +80°C / -40 to 176°F Storage: -40 to +85°C / -40 to 185°F

Relative humidity: 95% non-condensing

at +40°C / +104°F

Water and dust (IP-rating)

Transceiver **TP30** IP56 Antenna:



Live streaming - or store-and-forward

Facilitates both live streaming and store-andforward and enables direct transmissions from the hot spots of the world. Utilize the highest streaming rates available on BGAN with BGAN X-Stream when the terminal is standing still (on-the-pause).

Power

DC input range: 10.5-32VDC

Power (max)@10.5-32V.: 150W

(incl. antenna & PoE output)

Other features

Telephone Functionality

Phone book, message indication, restricted dialing and traffic logging.

Set-up and Router Functionality

Webserver, Built-in NAT Router, Admin control (password protected), DHCP, Network Management, Remote Management, SIP Server, Point-to-Point Protocol over Ethernet (PPPoE), Power over Ethernet (PoE)

Package

EXPLORER 727 transceiver

EXPLORER 727 tracking antenna

Antenna cable, coax w/ TNC plug (2.7m & 8m / 8.8ft & 26ft)

Standard ethernet cable (5m / 16.4ft)

24V DC input cable (6m / 19.7ft) with 5 additional wires

for I/O connectors

Thrane IP handset w/ cradle & coiled cable

Antenna mounting kit (fixed / rail)

Getting started kit: Quick start guide, CD with manuals

Product number

403722A-20000 EXPLORER 727 System, white antenna 403722A-00700 EXPLORER 727 System,

desert sand antenna

403722A-20010 EXPLORER 727 System, 19" rack version, white antenna

403722A-00710 EXPLORER 727 System,

19" rack version, desert sand antenna

For further information please contact:

Ground Control www.groundcontrol.com Tel: +1.805.783.4600 sales@groundcontrol.com

